

SPOT ARM

BostonDynamics



Meet the mobile robot arm designed to enable you to **act on data insights** and **perform real, physical work** in human-centric environments.

Equipped to operate through both **semi-autonomous actions** and **telematics**, the arm will open doors, pick, place, push or drag objects, and adapt to various situations at the touch of a button or **swipe of a screen**.



Génération
ROBOTS

Official distributor

www.generationrobots.com

gr@generationrobots.com

+33 5 56 39 37 05

SPOT ARM



TABLET BEHAVIORS

GRASPING, PICKING, PLACING

Manually or semi-autonomously grasp, lift, carry, place, and drag a wide variety of objects, including valve handles, door knobs, tools, etc.

CONSTRAINED MANIPULATION Semi-autonomously manipulate objects with constrained movement (e.g. turn valves, pull levers, open drawers, etc.).

DOOR OPENING

Semi-autonomously turn handles and open standard push and pull doors.

API OPTIONS

JOINT-SPACE CONTROL

- Specify joint angles and velocities
- Move to predefined configurations

END-EFFECTOR CONTROL

- Specify position, velocity, and force trajectories in Cartesian space
- Point the end-effector at a point in the world
- Perform tasks in contact with the environment (e.g. drawing, wiping, etc.)

SPOT ARM

SPECIFICATIONS

GENERAL

Degrees of Freedom 6 + gripper
Length (at full extension) 984 mm (38.7 in)
Mass/Weight 8 kg (17.6 lbs)
(including gripper)
Max. Endpoint Speed 10 m/s
Max. Lift Capacity* Up to 11 kg (24.3 lbs)
Continuous Lift Capacity* 5 kg (11 lbs)
(at 0.5 m extension)
Max. Drag Capacity* Up to 25 kg (55.1 lbs)
(on carpet)

ON ROBOT

Total Mass/Weight 39.7 kg (87.5 lbs)
Max. Reach Height 1800 mm (70.9 in)

*Payload capacities measured at 22°C

GRIPPER

Depth 90 mm (3.5 in)
Max Aperture 175 mm (6.9 in)
Peak Clamp Force (at tip of opening) 130 N
Integrated Sensors ToF, IMU, 4K RGB
Accessory Port Gigabit Ethernet, 50W power, camera sync (PPS)

ENVIRONMENT

Operating Temp. -20°C to 45°C
Ingress Protection Water and dust resistant



JOINT RANGE OF MOTION + LINK LENGTHS (mm)

